

TECHNICAL INFORMATION

Tamturbo® Touch-Free™ Compressors

Touch-Free. Oil-Free. Care-Free.

PRESSURE RANGE 5-9 BAR (75-130 PSI)

Model	Working pressure		Free air delivery		Input power		Nominal power		Dimensions (Width / Length / Height)		Sound level dB(A)	Cooling
	bar	psi	m ³ /min	cfm	kW	hp	kW	hp	mm	inch		
TT145	5-9	75-130	8.0-20.2 12.8-28.0 10.4-28.4	290-720 460-990 370-1010	54-199	72-267	145	200	1821 2173 2059	71.7 85.6 81.1	76	Liquid / Air (optional)
TT185	5-9	75-130	14.2-33.0	510-1170	81-236	109-316	185	250	1821 2173 2059	71.7 85.6 81.1	76	Liquid / Air (optional)
TT225	5-9	75-130	20.5-37.6	730-1330	131-256	176-343	225	306	1821 2173 2059	71.7 85.6 81.1	76	Liquid / Air (optional)
TT325	5-9	75-130	22.5-53.3	800-1890	129-351	173-470	325	440	2489 2021 2022	98.0 79.6 79.6	76	Liquid / Air (optional)

PRESSURE RANGE 2-5 BAR (30-75 PSI)

Model	Working pressure		Free air delivery		Input power		Nominal power		Dimensions (Width / Length / Height)		Sound level dB(A)	Cooling
	bar	psi	m ³ /min	cfm	kW	hp	kW	hp	mm	inch		
TT115	2-5	30-75	6.6-20.3 10.4-28.1 8.5-28.4	240-720 370-1000 310-1010	30-145	41-194	115	155	1821 2173 2059	71.7 85.6 81.1	76	Liquid / Air (optional)
TT135	2-4.5	30-65	12.2-33.0	440-1170	47-155	63-207	135	180	1821 2173 2059	71.7 85.6 81.1	76	Liquid / Air (optional)
TT235	2-5	30-75	16.9-56.6	600-2000	63-246	84-329	235	320	2489 2021 2022	98.0 79.6 79.6	76	Liquid / Air (optional)

ENERGY RECOVERY - STANDARD FEATURE

Cooling liquid outlet temperature 15-65 °C (60-150 °F)

Cooling liquid inlet temperature 5-35 °C (40-95 °F)

Ambient and inlet air temperature 5-40 °C (40-105 °F)

Tamturbo
JUST AIR

Tel +1 (314) 576-9001 Americas

Tel +358 (0)10 423 2303 Global

info@tamturbo.com

www.tamturbo.com

This publication is for general informational purposes only and should not be construed as a representation or warranty on any subject matter, products or specifications. Tamturbo reserves the right at any time, without notice, to alter or discontinue the products and/or specifications referenced herein. This publication creates no warranty on the part of Tamturbo, express or implied, including but not limited to any implied warranty or merchantability or fitness for a particular purpose. Tamturbo is a registered trademark of Tamturbo Plc. Tamturbo Plc. reserves the right to make changes to product(s) described herein without prior notice. © Copyright Tamturbo Plc. 2019. Patents pending.

